


HabasitLINK® sprockets – 1 1/2" pitch belting

ST615, VT615



Molded sprocket

Machined sprocket

Sprocket part number	Number of teeth	(PD) Nominal pitch diameter		(WH) Shaft center to top of wearstrip		(BH) Shaft center to top of belt		(HT) Hub thickness	
		inch	mm	inch	mm	inch	mm	inch	mm
ST71509M	9	4.39	111.5	1.81	46.04	2.31	58.74	1.50	38.1
ST71512M	12	5.80	147.3	2.55	64.80	3.05	77.50	1.50	38.1
ST71515	15	7.21	183.4	3.28	83.34	3.78	96.04	1.00	25.4
ST71517	17	8.16	207.3	3.76	95.52	4.26	108.2	1.00	25.4

M = molded sprocket

Split sprockets and other tooth sizes are available. Standard machined sprocket material is UHMW, Nylon and Urethane are available.

Sprocket part number	Available bore size															
	25 mm	1"	1" sq.	30 mm	1-1/4"	1-7/16"	1-1/2"	1-1/2" sq.	40 mm	40 mm sq.	1-15/16"	50 mm	2" sq.	60 mm	60 mm sq.	2-1/2" sq.
ST71509M	-	✓	-	✓	✓	✓	✓	✓	-	✓	-	-	-	-	-	-
ST71512M	-	✓	-	✓	✓	✓	✓	✓	-	✓	-	-	-	-	-	-
ST71515	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ST71517	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

M = molded sprocket

All bore sizes are round bore unless designated square (sq.).