



## SLIDEKIT-UR-PE-2500-11-SFM-S00 [↗](#)

### Información técnica

#### Información adicional

|                                      |                       |
|--------------------------------------|-----------------------|
| 12.100 N                             |                       |
| Controll box = IP64<br>SlideKit =N/A | Type of protection IP |

#### Medidas principales y datos de rendimiento

|                |            |                      |
|----------------|------------|----------------------|
|                | 2.500 mm   | Stroke               |
| A              | 3.200 mm   |                      |
| B              | 16 mm      |                      |
| C              | 65 mm      |                      |
| D              | 3.000 mm   |                      |
| E              | 165 mm     |                      |
| M <sub>x</sub> | 2.400 Nm   | Max. dynamic moments |
|                | 1.800 Nm   | Max. dynmic moment   |
|                | 10.900 N   | Max. dynamic payload |
|                | 95 %       | Humidity             |
|                | Belt drive | Drive type           |

#### Rango de temperatura

|  |       |                          |
|--|-------|--------------------------|
|  | 0 °C  | Ambient temperature min. |
|  | 50 °C | Ambient Temperatur max.  |

#### General characteristic values

|  |                      |
|--|----------------------|
| UR3, UR5, UR10,<br>UR16, CB-Series<br>and e-Series | Robots compatibility |
|--|----------------------|