

**W12-H6-RROC**

Eje macizo

solid shafts, with axial and/or radial threaded holes

Información técnica



Variante de su producto actual

Size code	12	
Tolerance diameter	H6	
Material	CF53	Heat treatable steel (material no.:1.1213)
Recubrimiento	RROC	Special coating Corroctect, anti corrosion protection

Medidas principales y datos de rendimiento

d_{LW}	12 mm	Diameter Shaft
L_{max}	6.000 mm	Length total maximum
$\approx m$	0,89 kg/m	Peso

Medidas de montaje

$d_{LW Tol}$	h6	Diameter Shaft
$h6 Tol$	0 μm	Diameter Shaft high
$h6 Tol$	-11 μm	Diameter Shaft low
SHD min	0,6 mm	Surface Hardness Depth
t_1	5 μm	Roundness
t_2	8 μm	Parallelism



Medidas principales

G 2	M4/M5	Axial thread (size)
G 7	M4	Radial thread (size)
B 01	M4/M5	Drilling pattern axial thread one side
B 02	M4/M5	Drilling pattern axial thread both side
B 03	M4	Drilling pattern radial thread
B 04	M4+M4-M5	Drilling pattern radial thread+axial thread one side
B 05	M4+M4-M5	Drilling pattern radial thread+axial thread both side