



IMAGE
COMING SOON**KTSG25-PP-AS**

Unidad de rodamiento lineal de bolas

Linear ball bearing and housing unit; with self-aligning linear ball bearing, contact seals on both sides

Información técnica



Variante de su producto actual

Size code	25
Seal	PP
n.r.	

AS

Relubrication facility


≈m

1,15 kg

Peso

Medidas principales y datos de rendimiento

F _w	25 mm	Diameter of ball complement
H	60 mm	Height
L	122 mm	Longitud
B	78 mm	Anchura
C _{max}	6.400 N	Load capacity dyn.
C _{0 max}	8.600 N	Load capacity stat.

**Medidas de montaje**

J _B	60 mm	
Tol J _B	+ 0,15 mm	Upper tolerance
Tol J _B	- 0,15 mm	Lower tolerance
B ₁	59,4 mm	
A ₅	39 mm	Mounting Dimension
Tol A ₅	+ 0,01 mm	Upper tolerance
Tol A ₅	- 0,01 mm	Lower tolerance
J _L	94 mm	Distance
Tol J _L	+ 0,15 mm	Upper tolerance
Tol J _L	- 0,15 mm	Lower tolerance
L ₆	44 mm	Distance
H ₂	30 mm	Center height
Tol H ₂	+ 0,008 mm	Upper tolerance
Tol H ₂	- 0,016 mm	Lower tolerance
H ₄	41,5 mm	Mounting Dimension
H ₅	8,3 mm	
T ₅	22 mm	Mounting Dimension
H ₆	29 mm	
G ₂	M10	
N ₁	8,4 mm	Mounting Dimension
N ₄	6 mm	
N ₃	15 mm	
K ₅	M8	
K ₈	NIP5MZ	Lubrication nipple
	8	Ball rows