


**W25-H6-RROC**

Eje macizo

solid shafts, with axial and/or radial threaded holes

## Información técnica



## Variante de su producto actual

Size code	25	
Tolerance diameter	H6	
Material	CF53	Heat treatable steel (material no.:1.1213)
Recubrimiento	RROC	Special coating Corrotect, anti corrosion protection

## Medidas principales y datos de rendimiento

$d_{LW}$	25 mm	Diameter Shaft
$L_{max}$	6.000 mm	Length total maximum
$\approx m$	3,85 kg/m	Peso

## Medidas de montaje

$d_{LW Tol}$	h6	Diameter Shaft
$h6 Tol$	0 $\mu m$	Diameter Shaft high
$h6 Tol$	-13 $\mu m$	Diameter Shaft low
SHD min	0,9 mm	Surface Hardness Depth
$t_1$	6 $\mu m$	Roundness
$t_2$	9 $\mu m$	Parallelism



### Medidas principales

G 2	M8-M10-M12	Axial thread (size)
G 7	M6/M8	Radial thread (size)
B 01	M8/M10/M12	Drilling pattern axial thread one side
B 02	M8/M10/M12	Drilling pattern axial thread both side
B 03	M6/M8	Drilling pattern radial thread
B 04	M6/M8 + M8/M10/ M12	Drilling pattern radial thread+axial thread one side
B 05	M6/M8 + M8/M10/ M12	Drilling pattern radial thread+axial thread both side