


**W30-H6-X46**

Eje macizo

solid shafts, with axial and/or radial threaded holes

Información técnica



Variante de su producto actual

Size code	30	
Tolerance diameter	H6	
Material	X46	Corrosion-resistant steel (material no.:1.4034)

Medidas principales y datos de rendimiento

d _{LW}	30 mm	Diameter Shaft
L _{max}	6.000 mm	Length total maximum
≈m	5,55 kg/m	Peso

Medidas de montaje

d _{LW Tol}	h6	Diameter Shaft
h6 Tol	0 μm	Diameter Shaft high
h6 Tol	-13 μm	Diameter Shaft low
SHD min	0,9 mm	Surface Hardness Depth
t ₁	6 μm	Roundness
t ₂	9 μm	Parallelism



Medidas principales

G 2	M10-M12-M16	Axial thread (size)
G 7	M6/M10	Radial thread (size)
B 01	M10/M12/M16	Drilling pattern axial thread one side
B 02	M10/M12/M16	Drilling pattern axial thread both side
B 03	M6/M10	Drilling pattern radial thread
B 04	M6/M10 + M10/M12/ M16	Drilling pattern radial thread+axial thread one side
B 05	M6/M10 + M10/M12/ M16	Drilling pattern radial thread+axial thread both side