


**W50-H6-CF53**

Eje macizo

solid shafts, with axial and/or radial threaded holes

## Información técnica



## Variante de su producto actual

Size code	50
Tolerance diameter	H6
Material	CF53 Heat treatable steel (material no.:1.1213)

## Medidas principales y datos de rendimiento

d <sub>LW</sub>	50 mm	Diameter Shaft
L <sub>max</sub>	6.000 mm	Length total maximum
≈m	15,41 kg/m	Peso

## Medidas de montaje

d <sub>LW Tol</sub>	h6	Diameter Shaft
h6 <sub>Tol</sub>	0 μm	Diameter Shaft high
h6 <sub>Tol</sub>	-16 μm	Diameter Shaft low
SHD <sub>min</sub>	1,5 mm	Surface Hardness Depth
t <sub>1</sub>	7 μm	Roundness
t <sub>2</sub>	11 μm	Parallelism



### Medidas principales

G 2	M12/M16/M20	Axial thread (size)
G 7	M12/M14	Radial thread (size)
B 01	M12/M16/M20	Drilling pattern axial thread one side
B 02	M12/M16/M20	Drilling pattern axial thread both side
B 03	M12/M14	Drilling pattern radial thread
B 04	M12/M14 + M12/ M16/M20	Drilling pattern radial thread+axial thread one side
B 05	M12/M14 + M12/ M16/M20	Drilling pattern radial thread+axial thread both side