

**MLF52-245-E-ZR-FBALG** [↗](#)

Módulo lineal

Actuators with external track roller guidance system and toothed belt drive. With bellows

Información técnica



Variante de su producto actual

| | | |
|---------------------|-------|------------------------|
| Size code | 52 | |
| Length of carriage | 245 | 245 mm |
| Carriage design | E | Strengthened carriage |
| Drive type | (3)ZR | Toothed belt drive |
| Additional carriage | / | No additional carriage |
| Support rail design | / | One-piece |
| Bellow | FBALG | Yes |

Medidas principales y datos de rendimiento

| | | |
|----------------|--------|-------------|
| B ₁ | 145 mm | Total Width |
| H | 125 mm | Altura |
| L | 245 mm | Longitud |



Medidas de montaje

| | | |
|--------------|---------|------------------|
| D 86 | 95 mm | |
| D 87 | 115 mm | Ø Bolt circle |
| d 85 | 20 mm | |
| d 86 | 76 mm | Ø Inner Fit |
| L 88 | 31 mm | |
| G 43 | M10 | Thread |
| G 87 | M8 | Thread |
| h 85 | 60,6 mm | |
| J B43 | 105 mm | |
| J L43 | 160 mm | Tolerance ±0,2 |
| j B8 | 80 mm | |
| N B85 | 6 mm | Width of Keyway |
| N L85 | 25 mm | Length of Keyway |
| N T85 | 3,5 mm | Depth of Keyway |
| T 86 | 4 mm | Depth Fit |
| Tol T 86 up | 0,5 mm | Upper tolerance |
| Tol T 86 low | 0 mm | Lower tolerance |
| t 43 max | 24 mm | Depth of Thread |
| t 87 max | 15 mm | |





Medidas

| | | |
|--------------------|----------|-----------------------------------|
| B ₂ | 112 mm | Width of Support Rail |
| B ₄ | 111 mm | Width of Return Unit |
| B ₇₂ | 2 mm | |
| H ₁ | 53,8 mm | |
| H ₂ | 98,6 mm | Altura |
| H ₄ | 118,3 mm | Height of Return Unit |
| H ₇ | 65,4 mm | |
| h ₁₃ | 25 mm | |
| h ₁₄ | 50 mm | |
| L _{2 max} | 8.000 mm | Maximum length of Support Rail |
| L ₄ | 115,5 mm | |
| F _{BL} | 1,37 | Effective length factor of bellow |
| S | 85 mm | Medida |





Datos técnicos

| | | |
|---------------------|---------------------|--|
| m_{LAW} | 3,4 kg | Mass of Carriage |
| v_{max} | 8 m/s | Maximum Speed |
| a_{max} | 40 m/s ² | Maximum Acceleration |
| R_x | 105 mm | |
| R_y | 35,3 mm | |
| R_z | 90 mm | |
| I C | 17.800 N | Load direction I: compressive load |
| I C ₀ | 8.900 N | Load direction I: compressive load |
| II C | 17.800 N | Load direction II: tensile load |
| II C ₀ | 8.900 N | Load direction II: tensile load |
| III C | 28.400 N | Load direction III: lateral load |
| III C ₀ | 15.500 N | Load direction III: lateral load |
| M _{0x per} | 180 Nm | Max. permissible static moment per Carriage |
| M _{0y per} | 800 Nm | Max. permissible static moment per Carriage |
| M _{0z per} | 460 Nm | Max. permissible static moment per Carriage |
| I _y | 386 cm ⁴ | Geometrical moments of inertia of Support Rail |
| I _z | 301 cm ⁴ | Geometrical moments of inertia of Support Rail |

Información adicional

| | | |
|--|-------------------------|--|
| | 73,5 Nm | Max. permissible drive torque |
| | 4 x LFR5301-10-2Z | Track Rollers |
| | 0,1 mm | Repeat Accuracy ± |
| | 270 mm | Feed (mm/rotation) |
| | 32AT10 | Toothed Belt |
| | 0,2 kg/m | Mass of Toothed Belt |
| | 1.750 N | Permissible Toothed Belt operating force |
| | 12,6 kg*cm ² | Mass moment of inertia of Gears |



Rango de temperatura

| | | |
|------------------|------|------------------------------|
| T _{min} | 0 °C | Minimum operating Temperatur |
|------------------|------|------------------------------|

| | | |
|------------------|-------|------------------------------|
| T _{max} | 80 °C | Maximum operating Temperatur |
|------------------|-------|------------------------------|