



**FAG**

## S2BCH-200MM-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	200 mm	Diámetro del eje
H	≈ 606,425 mm	Housing height
B	≈ 685,8 mm	Length base
≈m	293,02 kg	Peso



## Medidas

	S2BCH-200MM-FL	Complete unit float
	S2BCH-200MM-HD	Complete unit held
	PH-24	Housing designation
A	≈ 304,8 mm	Center height
C	≈ 266,7 mm	Base width
D	≈ 50,8 mm	Base height
E <sub>min</sub>	≈ 488,95 mm	Base hole distance 1 min
E <sub>min</sub>	≈ 527,05 mm	Base hole distance 1 max
F	≈ 190,5 mm	Base hole distance 2
s	4	# of mounting bolts
s	≈ 31,75 mm	Mounting bolt diameter
	S2BC-200MM-FL	Cartridge float bearing
	S2BC-200MM-HD	Cartridge held bearing
	S2C-800	Cartridge
G	≈ 255,587 mm	Length through bore
L	≈ 425,45 mm	Outside diameter cartridge
	≈ 2,676 kg	Grease capacity
	≈ 156,444 kg	Cartridge weight
	S2B-200MM-FL	Bearing float
	S2B-200MM-HD	Bearing held
	≈ 60,781 kg	Bearing weight
	800 Grp	Bearing group
C <sub>r</sub>	≈ 889.644,48 N	Capacidad de carga dinámica, radial
C <sub>0r</sub>	≈ 1.449.585,408 N	Capacidad de carga estática, radial
C <sub>a</sub>	≈ 55.604,448 N	Capacidad de carga dinámica, axial
	1.188 1/min	Limiting speed
D <sub>0</sub>	≈ 368,3 mm	Outside diameter bearing
C <sub>0</sub>	≈ 155,981 mm	Width inner ring
B <sub>0</sub>	≈ 90,5 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 07:10:18 UTC

SCHAEFFLER

