




FAG

S1BCH-340MM-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	340 mm	Diámetro del eje
B	≈ 850,9 mm	Length base
H	≈ 774,7 mm	Housing height
≈m	498,951 kg	Peso



Medidas

	S1BCH-340MM-FL	Complete unit float
	S1BCH-340MM-HD	Complete unit held
	PH-19	Housing designation
A	≈ 387,35 mm	Center height
C	≈ 254 mm	Base width
D	≈ 57,15 mm	Base height
E _{min}	≈ 635 mm	Base hole distance 1 min
E _{max}	≈ 673,1 mm	Base hole distance 1 max
F	≈ 165,1 mm	Base hole distance 2
S	4	# of mounting bolts
S	≈ 38,1 mm	Mounting bolt diameter
	S1BC-340MM-FL	Cartridge float bearing
	S1BC-340MM-HD	Cartridge held bearing
	S1C-1400	Cartridge
G	≈ 266,7 mm	Length through bore
L	≈ 546,1 mm	Outside diameter cartridge
	≈ 3,039 kg	Grease capacity
	≈ 215,865 kg	Cartridge weight
	S1B-340MM-FL	Bearing float
	S1B-340MM-HD	Bearing held
	≈ 63,049 kg	Bearing weight
	1400 Grp	Housing group
C _r	≈ 780.846,4 N	Capacidad de carga dinámica, radial
C _{0r}	≈ 1.624.187,2 N	Capacidad de carga estática, radial
C _a	≈ 42.015,808 N	Capacidad de carga dinámica, axial
	805 1/min	Limiting speed
D ₀	≈ 488,95 mm	Outside diameter bearing
C ₀	≈ 135,941 mm	Width inner ring
B ₀	≈ 74,6 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 10:22:16 UTC

SCHAEFFLER

