



FAG

S1BCH-320MM-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	320 mm	Diámetro del eje
B	≈ 812,8 mm	Length base
H	≈ 736,6 mm	Housing height
≈m	417,305 kg	Peso



Medidas

	S1BCH-320MM-FL	Complete unit float
	S1BCH-320MM-HD	Complete unit held
	PH-18	Housing designation
A	≈ 368,3 mm	Center height
C	≈ 254 mm	Base width
D	≈ 53,975 mm	Base height
E _{min}	≈ 603,25 mm	Base hole distance 1 min
E _{max}	≈ 641,35 mm	Base hole distance 1 max
F	≈ 177,8 mm	Base hole distance 2
S	4	# of mounting bolts
S	≈ 38,1 mm	Mounting bolt diameter
	S1BC-320MM-FL	Cartridge float bearing
	S1BC-320MM-HD	Cartridge held bearing
	S1C-1300	Cartridge
G	≈ 298,45 mm	Length through bore
L	≈ 527,05 mm	Outside diameter cartridge
	≈ 2,722 kg	Grease capacity
	≈ 199,989 kg	Cartridge weight
	S1B-320MM-FL	Bearing float
	S1B-320MM-HD	Bearing held
	≈ 57,153 kg	Bearing weight
	1300 Grp	Housing group
C _r	≈ 785.645,792 N	Capacidad de carga dinámica, radial
C _{0r}	≈ 1.605.447,776 N	Capacidad de carga estática, radial
C _a	≈ 44.502,24 N	Capacidad de carga dinámica, axial
	856 1/min	Limiting speed
D ₀	≈ 463,804 mm	Outside diameter bearing
C ₀	≈ 135,941 mm	Width inner ring
B ₀	≈ 74,6 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 10:24:07 UTC

SCHAEFFLER

