



FAG

S2BCH-150MM-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----|------------|------------------|
| d | 150 mm | Diámetro del eje |
| H | ≈ 457,2 mm | Housing height |
| B | ≈ 635 mm | Length base |
| ≈m | 169,643 kg | Peso |



Medidas

| | | |
|------------------|-------------------|-------------------------------------|
| | S2BCH-150MM-FL | Complete unit float |
| | S2BCH-150MM-HD | Complete unit held |
| | PH-21 | Housing designation |
| A | ≈ 311,15 mm | Center height |
| C | ≈ 203,2 mm | Base width |
| D | ≈ 50,8 mm | Base height |
| E _{min} | ≈ 546,1 mm | Base hole distance 1 min |
| E _{min} | ≈ 571,5 mm | Base hole distance 1 max |
| F | ≈ 127 mm | Base hole distance 2 |
| s | 4 | # of mounting bolts |
| s | ≈ 25,4 mm | Mounting bolt diameter |
| | S2BC-150MM-FL | Cartridge float bearing |
| | S2BC-150MM-HD | Cartridge held bearing |
| | S2C-600 | Cartridge |
| G | ≈ 201,612 mm | Length through bore |
| L | ≈ 336,55 mm | Outside diameter cartridge |
| | ≈ 1,361 kg | Grease capacity |
| | ≈ 73,482 kg | Cartridge weight |
| | S2B-150MM-FL | Bearing float |
| | S2B-150MM-HD | Bearing held |
| | ≈ 31,933 kg | Bearing weight |
| | 600 Grp | Bearing group |
| C _r | ≈ 655.306,048 N | Capacidad de carga dinámica, radial |
| C _{0r} | ≈ 1.019.939,744 N | Capacidad de carga estática, radial |
| C _a | ≈ 5.061,824 N | Capacidad de carga dinámica, axial |
| | 1.450 1/min | Limiting speed |
| D ₀ | ≈ 292,1 mm | Outside diameter bearing |
| C ₀ | ≈ 123,825 mm | Width inner ring |
| B ₀ | ≈ 68,275 mm | Width outer ring |





Ver detalles del producto en Medias

13.11.2025, 07:00:40 UTC

SCHAEFFLER

