



FAG

S2BCH-190MM-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	190 mm	Diámetro del eje
H	≈ 606,425 mm	Housing height
B	≈ 685,8 mm	Length base
≈m	293,02 kg	Peso



Medidas

	S2BCH-190MM-FL	Complete unit float
	S2BCH-190MM-HD	Complete unit held
	PH-24	Housing designation
A	≈ 304,8 mm	Center height
C	≈ 266,7 mm	Base width
D	≈ 50,8 mm	Base height
E _{min}	≈ 488,95 mm	Base hole distance 1 min
E _{min}	≈ 527,05 mm	Base hole distance 1 max
F	≈ 190,5 mm	Base hole distance 2
s	4	# of mounting bolts
s	≈ 31,75 mm	Mounting bolt diameter
	S2BC-190MM-FL	Cartridge float bearing
	S2BC-190MM-HD	Cartridge held bearing
	S2C-800	Cartridge
G	≈ 255,587 mm	Length through bore
L	≈ 425,45 mm	Outside diameter cartridge
	≈ 2,676 kg	Grease capacity
	≈ 156,444 kg	Cartridge weight
	S2B-190MM-FL	Bearing float
	S2B-190MM-HD	Bearing held
	≈ 60,781 kg	Bearing weight
	800 Grp	Bearing group
C _r	≈ 889.644,48 N	Capacidad de carga dinámica, radial
C _{0r}	≈ 1.449.585,408 N	Capacidad de carga estática, radial
C _a	≈ 55.604,448 N	Capacidad de carga dinámica, axial
	1.188 1/min	Limiting speed
D ₀	≈ 368,3 mm	Outside diameter bearing
C ₀	≈ 155,981 mm	Width inner ring
B ₀	≈ 90,5 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 07:06:13 UTC

SCHAEFFLER

