



FAG

S2BCH-215-HD-2B [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	2 ¹⁵ / ₁₆ in	Shaft diameter
H	10 ¹ / ₁₆ in	Housing height
B	15 ⁰ / ₁ in	Length base
≈m	66,599 lbs	Peso



Medidas

	S2BCH-215-FL-2B	Complete unit float
	S2BCH-215-HD-2B	Complete unit held
	PH-5-2B	Housing designation
A	4 ³ / ₈ in	Center height
C	3 ¹ / ₂ in	Base width
D	1 ³ / ₄ in	Base height
E _{min}	12 ³ / ₁₆ in	Base hole distance 1 min
E _{min}	13 ³ / ₁₆ in	Base hole distance 1 max
s	2	# of mounting bolts
s	³ / ₄ in	Mounting bolt diameter
	S2BC-215-FL	Cartridge float bearing
	S2BC-215-HD	Cartridge held bearing
	S2C-300	Cartridge
G	5 ¹ / ₂ in	Length through bore
L	7 ⁰ / ₁ in	Outside diameter cartridge
	656,1 lbs	Grease capacity
	34 lbs	Cartridge weight
	S2B-215-FL	Bearing float
	S2B-215-HD	Bearing held
	12,1 lbs	Bearing weight
	300 Grp	Bearing group
C _r	45.440 lbf	Capacidad de carga dinámica, radial
C _{0r}	59.277 lbf	Capacidad de carga estática, radial
C _a	561 lbf	Capacidad de carga dinámica, axial
	2.930 1/min	Limiting speed
D ₀	5 ⁷ / ₈ in	Outside diameter bearing
C ₀	3 ¹ / ₄ in	Width inner ring

