




FAG

S1BCH-304-FL-2B

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	3 1/4 in	Shaft diameter
B	15 0/1 in	Length base
H	10 1/16 in	Housing height
≈m	57,999 lbs	Peso



Medidas

	S1BCH-304-FL-2B	Complete unit float
	S1BCH-304-HD-2B	Complete unit held
	PH-5-2B	Housing designation
A	4 3/8 in	Center height
C	3 1/2 in	Base width
D	1 3/4 in	Base height
E min	12 3/16 in	Base hole distance 1 min
E max	13 3/16 in	Base hole distance 1 max
S	2	# of mounting bolts
S	3/4 in	Mounting bolt diameter
	S1BC-304-FL	Cartridge float bearing
	S1BC-304-HD	Cartidge held bearing
	S1C-308	Cartridge
G	5 3/16 in	Length through bore
L	7 0/1 in	Outside diameter cartridge
	656,1 lbs	Grease capacity
	25,5 lbs	Cartridge weight
	S1B-304-FL	Bearing float
	S1B-304-HD	Bearing held
	9,2 lbs	Bearing weight
	308 Grp	Housing group
C _r	37.301 lbf	Capacidad de carga dinámica, radial
C _{0r}	52.396 lbf	Capacidad de carga estática, radial
C _a	450 lbf	Capacidad de carga dinámica, axial
	2.740 1/min	Limiting speed
D ₀	6 0/1 in	Outside diameter bearing
C ₀	2 3/4 in	Width inner ring

