



FAG

S2BCH-608-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	6 1/2 in	Shaft diameter
H	21 0/1 in	Housing height
B	23 1/2 in	Length base
≈m	406,999 lbs	Peso



Medidas

	S2BCH-608-FL	Complete unit float
	S2BCH-608-HD	Complete unit held
	PH-22	Housing designation
A	10 1/2 in	Center height
C	9 1/2 in	Base width
D	1 3/4 in	Base height
E min	16 7/8 in	Base hole distance 1 min
E min	18 3/8 in	Base hole distance 1 max
F	6 3/4 in	Base hole distance 2
s	4	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-608-FL	Cartridge float bearing
	S2BC-608-HD	Cartridge held bearing
	S2C-608	Cartridge
G	9 1/8 in	Length through bore
L	14 1/2 in	Outside diameter cartridge
	3,2 lbs	Grease capacity
	230,9 lbs	Cartridge weight
	S2B-608-FL	Bearing float
	S2B-608-HD	Bearing held
	93,5 lbs	Bearing weight
	608 Grp	Bearing group
C _r	156.220 lbf	Capacidad de carga dinámica, radial
C _{0r}	237.758 lbf	Capacidad de carga estática, radial
C _a	10.907 lbf	Capacidad de carga dinámica, axial
	1.407 1/min	Limiting speed
D ₀	12 1/2 in	Outside diameter bearing
	12 1/2 in	Width inner ring
B ₀	3 1/4 in	Width outer ring

