



**FAG**

## S1BCH-403-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	4 <sup>3</sup> / <sub>16</sub> in	Shaft diameter
B	18 <sup>3</sup> / <sub>4</sub> in	Length base
H	12 <sup>3</sup> / <sub>8</sub> in	Housing height
≈m	110 lbs	Peso



**Medidas**

	S1BCH-403-FL	Complete unit float
	S1BCH-403-HD	Complete unit held
	PH-7	Housing designation
A	5 5/8 in	Center height
C	6 3/4 in	Base width
D	2 3/8 in	Base height
E min	15 3/4 in	Base hole distance 1 min
E max	16 11/16 in	Base hole distance 1 max
F	4 1/2 in	Base hole distance 2
S	4	# of mounting bolts
S	3/4 in	Mounting bolt diameter
	S1BC-403-FL	Cartridge float bearing
	S1BC-403-HD	Cartridge held bearing
	S1C-408	Cartridge
G	5 9/16 in	Length through bore
L	9 1/8 in	Outside diameter cartridge
	1,2 lbs	Grease capacity
	48,6 lbs	Cartridge weight
	S1B-403-FL	Bearing float
	S1B-403-HD	Bearing held
	20,8 lbs	Bearing weight
	408 Grp	Housing group
C <sub>r</sub>	62.784 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	93.994 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	650 lbf	Capacidad de carga dinámica, axial
	2.140 1/min	Limiting speed
D <sub>0</sub>	8 0/1 in	Outside diameter bearing
	1 13/16 in	Width inner ring
B <sub>0</sub>	1 13/16 in	Width outer ring

