



FAG

S2BCH-715-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	7 ¹⁵ / ₁₆ in	Shaft diameter
H	23 ⁷ / ₈ in	Housing height
B	27 ⁰ / ₁ in	Length base
≈m	645,998 lbs	Peso



Medidas

	S2BCH-715-FL	Complete unit float
	S2BCH-715-HD	Complete unit held
	PH-24	Housing designation
A	12 ⁰ / ₁ in	Center height
C	10 ¹ / ₂ in	Base width
D	2 ⁰ / ₁ in	Base height
E _{min}	19 ¹ / ₄ in	Base hole distance 1 min
E _{min}	20 ³ / ₄ in	Base hole distance 1 max
F	7 ¹ / ₂ in	Base hole distance 2
s	4	# of mounting bolts
s	1 ¹ / ₄ in	Mounting bolt diameter
	S2BC-715-FL	Cartridge float bearing
	S2BC-715-HD	Cartridge held bearing
	S2C-800	Cartridge
G	10 ¹ / ₁₆ in	Length through bore
L	16 ³ / ₄ in	Outside diameter cartridge
	5,9 lbs	Grease capacity
	344,9 lbs	Cartridge weight
	S2B-715-FL	Bearing float
	S2B-715-HD	Bearing held
	134 lbs	Bearing weight
	800 Grp	Bearing group
C _r	200.010 lbf	Capacidad de carga dinámica, radial
C _{0r}	325.896 lbf	Capacidad de carga estática, radial
C _a	12.501 lbf	Capacidad de carga dinámica, axial
	1.188 1/min	Limiting speed
D ₀	14 ¹ / ₂ in	Outside diameter bearing
	18 in	Width inner ring
B ₀	2 ⁹ / ₁₆ in	Width outer ring

