



FAG

S2BCH-411-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	4 ¹¹ / ₁₆ in	Shaft diameter
H	15 ³ / ₄ in	Housing height
B	22 ⁰ / ₁ in	Length base
≈m	234,001 lbs	Peso



Medidas

	S2BCH-411-FL	Complete unit float
	S2BCH-411-HD	Complete unit held
	PH-10	Housing designation
A	7 1/8 in	Center height
C	7 0/1 in	Base width
D	1 5/8 in	Base height
E min	18 1/2 in	Base hole distance 1 min
E min	20 1/2 in	Base hole distance 1 max
F	4 3/4 in	Base hole distance 2
s	4	# of mounting bolts
s	7/8 in	Mounting bolt diameter
	S2BC-411-FL	Cartridge float bearing
	S2BC-411-HD	Cartridge held bearing
	S2C-500	Cartridge
G	7 1/4 in	Length through bore
L	11 5/8 in	Outside diameter cartridge
	2,5 lbs	Grease capacity
	111,5 lbs	Cartridge weight
	S2B-411-FL	Bearing float
	S2B-411-HD	Bearing held
	55 lbs	Bearing weight
	500 Grp	Bearing group
C _r	111.370 lbf	Capacidad de carga dinámica, radial
C _{0r}	162.763 lbf	Capacidad de carga estática, radial
C _a	951 lbf	Capacidad de carga dinámica, axial
	1.780 1/min	Limiting speed
D ₀	10 0/1 in	Outside diameter bearing
	1 1/2 in	Width inner ring
B ₀	2 1/2 in	Width outer ring

