



**FAG**

## S2BCH-1108-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	11 1/2 in	Shaft diameter
H	31 0/1 in	Housing height
B	37 3/4 in	Length base
≈m	1.294,998 lbs	Peso



**Medidas**

	S2BCH-1108-FL	Complete unit float
	S2BCH-1108-HD	Complete unit held
	PH-28	Housing designation
A	15 1/2 in	Center height
C	13 0/1 in	Base width
D	2 3/8 in	Base height
E min	21 1/2 in	Base hole distance 1 min
E min	23 0/1 in	Base hole distance 1 max
E 1, min	29 1/2 in	Base hole distance 3 min
E 1, max	31 0/1 in	Base hole distance 3 max
F	10 0/1 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-1108-FL	Cartridge float bearing
	S2BC-1108-HD	Cartridge held bearing
	S2C-1200	Cartridge
G	12 1/16 in	Length through bore
L	21 3/4 in	Outside diameter cartridge
	11,8 lbs	Grease capacity
	599,8 lbs	Cartridge weight
	S2B-1108-FL	Bearing float
	S2B-1108-HD	Bearing held
	296,9 lbs	Bearing weight
	1200 Grp	Bearing group
C <sub>r</sub>	301.125 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	555.316 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	15.192 lbf	Capacidad de carga dinámica, axial
D <sub>0</sub>	10 1/2 in	Outside diameter bearing

