



**FAG**

## S3BCH-1400-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	14 <sup>0</sup> / <sub>1</sub> in	Shaft diameter
H	39 <sup>1</sup> / <sub>2</sub> in	Housing height
B	48 <sup>0</sup> / <sub>1</sub> in	Length base
≈m	2.529,995 lbs	Peso



**Medidas**

	S3BCH-1400-FL	Complete unit float
	S3BCH-1400-HD	Complete unit held
	PH-319	Housing designation
A	18 1/2 in	Center height
C	12 1/2 in	Base width
D	3 1/4 in	Base height
E min	24 7/8 in	Base hole distance 1 min
E max	27 0/1 in	Base hole distance 1 max
E 1, min	35 3/8 in	Base hole distance 3 min
E 1, max	37 1/2 in	Base hole distance 3 max
F	7 1/2 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/2 in	Mounting bolt diameter
	S3BC-1400-FL	Cartridge float bearing
	S3BC-1400-HD	Cartridge held bearing
	S3C-1400	Cartridge
G	17 0/1 in	Lenght through bore
L	27 3/4 in	Outside diameter cartridge
	33 lbs	Grease capacity
	1.550 lbs	Cartridge weight
	S3B-1400-FL	Bearing float
	S3B-1400-HD	Bearing held
	710 lbs	Bearing weight
	1400 Grp	Bearing Group
C <sub>r</sub>	573.035 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	1.021.889 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	21.760 lbf	Capacidad de carga dinámica, axial
D <sub>0</sub>	24 1/4 in	Outside diameter bearing

