



FAG

S2BCH-1508-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	15 ¹ / ₂ in	Shaft diameter
H	39 ⁰ / ₁ in	Housing height
B	46 ⁰ / ₁ in	Length base
≈m	2.199,995 lbs	Peso



Medidas

	S2BCH-1508-FL	Complete unit float
	S2BCH-1508-HD	Complete unit held
	PH-32	Housing designation
A	19 1/2 in	Center height
C	14 1/2 in	Base width
D	2 3/4 in	Base height
E min	27 15/16 in	Base hole distance 1 min
E min	29 1/2 in	Base hole distance 1 max
E 1, min	35 15/16 in	Base hole distance 3 min
E 1, max	37 1/2 in	Base hole distance 3 max
F	11 0/1 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-1508-FL	Cartridge float bearing
	S2BC-1508-HD	Cartridge held bearing
	S2C-1600	Cartridge
G	13 1/4 in	Length through bore
L	27 0/1 in	Outside diameter cartridge
	20 lbs	Grease capacity
	1.104,7 lbs	Cartridge weight
	S2B-1508-FL	Bearing float
	S2B-1508-HD	Bearing held
	462,9 lbs	Bearing weight
	1600 Grp	Bearing group
C _r	428.302 lbf	Capacidad de carga dinámica, radial
C _{0r}	850.032 lbf	Capacidad de carga estática, radial
C _a	17.998 lbf	Capacidad de carga dinámica, axial
D ₀	24 1/4 in	Outside diameter bearing

