



**FAG**

## S1BCH-1115-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	11 <sup>15</sup> / <sub>16</sub> in	Shaft diameter
B	30 <sup>0</sup> / <sub>1</sub> in	Length base
H	26 <sup>3</sup> / <sub>4</sub> in	Housing height
≈m	741,998 lbs	Peso



**Medidas**

	S1BCH-1115-FL	Complete unit float
	S1BCH-1115-HD	Complete unit held
	PH-17	Housing designation
A	13 1/2 in	Center height
C	10 0/1 in	Base width
D	2 0/1 in	Base height
E min	22 1/4 in	Base hole distance 1 min
E max	23 3/4 in	Base hole distance 1 max
F	7 0/1 in	Base hole distance 2
S	4	# of mounting bolts
S	1 1/4 in	Mounting bolt diameter
	S1BC-1115-FL	Cartridge float bearing
	S1BC-1115-HD	Cartridge held bearing
	S1C-1200	Cartridge
G	9 3/4 in	Length through bore
L	19 1/4 in	Outside diameter cartridge
	4,4 lbs	Grease capacity
	377,9 lbs	Cartridge weight
	S1B-1115-FL	Bearing float
	S1B-1115-HD	Bearing held
	123 lbs	Bearing weight
	1200 Grp	Housing group
C <sub>r</sub>	162.808 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	329.360 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	9.678 lbf	Capacidad de carga dinámica, axial
	915 1/min	Limiting speed
D <sub>0</sub>	17 1/4 in	Outside diameter bearing
	5 5/8 in	Width inner ring
B <sub>0</sub>	2 15/16 in	Width outer ring

