



FAG

S2BCH-600-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	6 ⁰ / ₁ in	Shaft diameter
H	18 ⁰ / ₁ in	Housing height
B	25 ⁰ / ₁ in	Length base
≈m	373,998 lbs	Peso



Medidas

	S2BCH-600-FL	Complete unit float
	S2BCH-600-HD	Complete unit held
	PH-21	Housing designation
A	11 1/4 in	Center height
C	8 0/1 in	Base width
D	2 0/1 in	Base height
E min	21 1/2 in	Base hole distance 1 min
E min	22 1/2 in	Base hole distance 1 max
F	5 0/1 in	Base hole distance 2
s	4	# of mounting bolts
s	1 0/1 in	Mounting bolt diameter
	S2BC-600-FL	Cartridge float bearing
	S2BC-600-HD	Cartridge held bearing
	S2C-600	Cartridge
G	7 15/16 in	Length through bore
L	13 1/4 in	Outside diameter cartridge
	3 lbs	Grease capacity
	162 lbs	Cartridge weight
	S2B-600-FL	Bearing float
	S2B-600-HD	Bearing held
	70,4 lbs	Bearing weight
	600 Grp	Bearing group
C _r	147.326 lbf	Capacidad de carga dinámica, radial
C _{0r}	229.303 lbf	Capacidad de carga estática, radial
C _a	1.138 lbf	Capacidad de carga dinámica, axial
	1.450 1/min	Limiting speed
D ₀	11 1/2 in	Outside diameter bearing
	1 1/8 in	Width inner ring
B ₀	2 5/8 in	Width outer ring

