



FAG

S3BCH-608-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	6 1/2 in	Shaft diameter
H	22 1/2 in	Housing height
B	29 0/1 in	Length base
≈m	787,997 lbs	Peso



Medidas

	S3BCH-608-FL	Complete unit float
	S3BCH-608-HD	Complete unit held
	PH-311	Housing designation
A	10 1/2 in	Center height
C	9 0/1 in	Base width
D	2 3/8 in	Base height
E min	24 0/1 in	Base hole distance 1 min
E max	25 1/2 in	Base hole distance 1 max
F	5 1/2 in	Base hole distance 2
s	4	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S3BC-608-FL	Cartridge float bearing
	S3BC-608-HD	Cartridge held bearing
	S3C-608	Cartridge
G	10 9/16 in	Lenght through bore
L	16 5/8 in	Outside diameter cartridge
	8 lbs	Grease capacity
	368 lbs	Cartridge weight
	S3B-608-FL	Bearing float
	S3B-608-HD	Bearing held
	169 lbs	Bearing weight
	608 Grp	Bearing Group
C _r	237.189 lbf	Capacidad de carga dinámica, radial
C _{0r}	360.515 lbf	Capacidad de carga estática, radial
C _a	15.462 lbf	Capacidad de carga dinámica, axial
	1.305 1/min	Limiting speed
D ₀	14 0/1 in	Outside diameter bearing
	11 1/2 in	Width inner ring
B ₀	4 1/2 in	Width outer ring

