



**FAG**

## S2BCH-607-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	6 <sup>7</sup> / <sub>16</sub> in	Shaft diameter
H	21 <sup>0</sup> / <sub>1</sub> in	Housing height
B	23 <sup>1</sup> / <sub>2</sub> in	Length base
≈m	406,999 lbs	Peso



**Medidas**

	S2BCH-607-FL	Complete unit float
	S2BCH-607-HD	Complete unit held
	PH-22	Housing designation
A	10 1/2 in	Center height
C	9 1/2 in	Base width
D	1 3/4 in	Base height
E min	16 7/8 in	Base hole distance 1 min
E min	18 3/8 in	Base hole distance 1 max
F	6 3/4 in	Base hole distance 2
s	4	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-607-FL	Cartridge float bearing
	S2BC-607-HD	Cartridge held bearing
	S2C-608	Cartridge
G	9 1/8 in	Length through bore
L	14 1/2 in	Outside diameter cartridge
	3,2 lbs	Grease capacity
	230,9 lbs	Cartridge weight
	S2B-607-FL	Bearing float
	S2B-607-HD	Bearing held
	93,5 lbs	Bearing weight
	608 Grp	Bearing group
C <sub>r</sub>	156.220 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	237.758 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	10.907 lbf	Capacidad de carga dinámica, axial
	1.407 1/min	Limiting speed
D <sub>0</sub>	12 1/2 in	Outside diameter bearing
	12,5 in	Width inner ring
B <sub>0</sub>	3 1/4 in	Width outer ring



La hoja de datos solo contiene una descripción general de los datos técnicos del producto seleccionado. Consulte la documentación adicional de este producto. Para más información, utilice el siguiente enlace en nuestra página web: [Formulario de contacto](#)