



FAG

S2BCH-1208-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	12 ¹ / ₂ in	Shaft diameter
H	33 ⁰ / ₁ in	Housing height
B	40 ⁰ / ₁ in	Length base
≈m	1.559,998 lbs	Peso



Medidas

	S2BCH-1208-FL	Complete unit float
	S2BCH-1208-HD	Complete unit held
	PH-29	Housing designation
A	16 1/2 in	Center height
C	11 1/2 in	Base width
D	2 1/2 in	Base height
E min	23 1/4 in	Base hole distance 1 min
E min	24 13/16 in	Base hole distance 1 max
E 1, min	31 1/4 in	Base hole distance 3 min
E 1, max	32 13/16 in	Base hole distance 3 max
F	8 1/4 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-1208-FL	Cartridge float bearing
	S2BC-1208-HD	Cartridge held bearing
	S2C-1300	Cartridge
G	13 0/1 in	Length through bore
L	23 1/8 in	Outside diameter cartridge
	16 lbs	Grease capacity
	689.8 lbs	Cartridge weight
	S2B-1208-FL	Bearing float
	S2B-1208-HD	Bearing held
	324.9 lbs	Bearing weight
	1300 Grp	Bearing group
C _r	309.649 lbf	Capacidad de carga dinámica, radial
C _{0r}	589.875 lbf	Capacidad de carga estática, radial
C _a	14.176 lbf	Capacidad de carga dinámica, axial
	78.4 lbf/in	Limiting speed
D ₀	20 3/4 in	Outside diameter bearing

