



FAG

S2BCH-1400-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	14 ⁰ / ₁ in	Shaft diameter
H	35 ¹ / ₂ in	Housing height
B	43 ⁰ / ₁ in	Length base
≈m	1.741,996 lbs	Peso



Medidas

	S2BCH-1400-FL	Complete unit float
	S2BCH-1400-HD	Complete unit held
	PH-30	Housing designation
A	17 ³ / ₄ in	Center height
C	14 ¹ / ₂ in	Base width
D	2 ¹ / ₂ in	Base height
E _{min}	25 ³ / ₁₆ in	Base hole distance 1 min
E _{min}	26 ³ / ₄ in	Base hole distance 1 max
E _{1, min}	33 ³ / ₁₆ in	Base hole distance 3 min
E _{1, max}	34 ³ / ₄ in	Base hole distance 3 max
F	11 ⁰ / ₁ in	Base hole distance 2
s	8	# of mounting bolts
s	1 ¹ / ₄ in	Mounting bolt diameter
	S2BC-1400-FL	Cartridge float bearing
	S2BC-1400-HD	Cartridge held bearing
	S2C-1400	Cartridge
G	13 ¹ / ₂ in	Length through bore
L	24 ³ / ₄ in	Outside diameter cartridge
	15,9 lbs	Grease capacity
	799,8 lbs	Cartridge weight
	S2B-1400-FL	Bearing float
	S2B-1400-HD	Bearing held
	404,9 lbs	Bearing weight
	1400 Grp	Bearing group
C _r	359.847 lbf	Capacidad de carga dinámica, radial
C _{0r}	683.122 lbf	Capacidad de carga estática, radial
C _a	16.057 lbf	Capacidad de carga dinámica, axial
D ₀	22 ¹ / ₄ in	Outside diameter bearing

