



**FAG**

## S2BCH-70MM-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	70 mm	Diámetro del eje
H	≈ 255,587 mm	Housing height
B	≈ 381 mm	Length base
≈m	33,566 kg	Peso



**Medidas**

	S2BCH-70MM-FL	Complete unit float
	S2BCH-70MM-HD	Complete unit held
	PH-5	Housing designation
A	≈ 111,919 mm	Center height
C	≈ 139,7 mm	Base width
D	≈ 44,45 mm	Base height
E <sub>min</sub>	≈ 314,325 mm	Base hole distance 1 min
E <sub>min</sub>	≈ 339,725 mm	Base hole distance 1 max
F	≈ 88,9 mm	Base hole distance 2
s	4	# of mounting bolts
s	≈ 19,05 mm	Mounting bolt diameter
	S2BC-70MM-FL	Cartridge float bearing
	S2BC-70MM-HD	Cartridge held bearing
	S2C-300	Cartridge
G	≈ 139,7 mm	Length through bore
L	≈ 177,8 mm	Outside diameter cartridge
	≈ 297,602 kg	Grease capacity
	≈ 15,422 kg	Cartridge weight
	S2B-70MM-FL	Bearing float
	S2B-70MM-HD	Bearing held
	≈ 5,488 kg	Bearing weight
	300 Grp	Bearing group
C <sub>r</sub>	≈ 202.117,12 N	Capacidad de carga dinámica, radial
C <sub>0r</sub>	≈ 263.664,096 N	Capacidad de carga estática, radial
C <sub>a</sub>	≈ 2.495,328 N	Capacidad de carga dinámica, axial
	2.930 1/min	Limiting speed
D <sub>0</sub>	≈ 149,225 mm	Outside diameter bearing
C <sub>0</sub>	≈ 82,55 mm	Width inner ring
B <sub>0</sub>	≈ 46,05 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 06:30:16 UTC

SCHAEFFLER

