




FAG

S2BCH-1500-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	15 ⁰ / ₁ in	Shaft diameter
H	36 ¹ / ₂ in	Housing height
B	43 ⁰ / ₁ in	Length base
≈m	1.852,996 lbs	Peso



Medidas

	S2BCH-1500-FL	Complete unit float
	S2BCH-1500-HD	Complete unit held
	PH-31	Housing designation
A	18 ¹ / ₄ in	Center height
C	14 ¹ / ₂ in	Base width
D	2 ⁵ / ₈ in	Base height
E _{min}	26 ¹ / ₁₆ in	Base hole distance 1 min
E _{min}	27 ⁵ / ₈ in	Base hole distance 1 max
E _{1, min}	34 ¹ / ₁₆ in	Base hole distance 3 min
E _{1, max}	35 ⁵ / ₈ in	Base hole distance 3 max
F	11 ⁰ / ₁ in	Base hole distance 2
s	8	# of mounting bolts
s	1 ¹ / ₄ in	Mounting bolt diameter
	S2BC-1500-FL	Cartridge float bearing
	S2BC-1500-HD	Cartridge held bearing
	S2C-1500	Cartridge
G	13 ¹ / ₂ in	Length through bore
L	25 ¹ / ₂ in	Outside diameter cartridge
	17 lbs	Grease capacity
	881.8 lbs	Cartridge weight
	S2B-1500-FL	Bearing float
	S2B-1500-HD	Bearing held
	409.9 lbs	Bearing weight
	1500 Grp	Bearing group
C _r	385.957 lbf	Capacidad de carga dinámica, radial
C _{0r}	761.112 lbf	Capacidad de carga estática, radial
C _a	16.923 lbf	Capacidad de carga dinámica, axial
D ₀	23 ⁰ / ₁₆ in	Outside diameter bearing

