



**FAG**

## S2BCH-1600-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	16 <sup>0</sup> / <sub>1</sub> in	Shaft diameter
H	39 <sup>0</sup> / <sub>1</sub> in	Housing height
B	46 <sup>0</sup> / <sub>1</sub> in	Length base
≈m	2.199,995 lbs	Peso



**Medidas**

	S2BCH-1600-FL	Complete unit float
	S2BCH-1600-HD	Complete unit held
	PH-32	Housing designation
A	19 1/2 in	Center height
C	14 1/2 in	Base width
D	2 3/4 in	Base height
E min	27 15/16 in	Base hole distance 1 min
E min	29 1/2 in	Base hole distance 1 max
E 1, min	35 15/16 in	Base hole distance 3 min
E 1, max	37 1/2 in	Base hole distance 3 max
F	11 0/1 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-1600-FL	Cartridge float bearing
	S2BC-1600-HD	Cartridge held bearing
	S2C-1600	Cartridge
G	13 1/4 in	Length through bore
L	27 0/1 in	Outside diameter cartridge
	20 lbs	Grease capacity
	1.104,7 lbs	Cartridge weight
	S2B-1600-FL	Bearing float
	S2B-1600-HD	Bearing held
	462,9 lbs	Bearing weight
	1600 Grp	Bearing group
C <sub>r</sub>	428.302 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	850.032 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	17.998 lbf	Capacidad de carga dinámica, axial
D <sub>0</sub>	24 1/4 in	Outside diameter bearing

