



**FAG**

## S2BCH-1500-HD [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	15 <sup>0</sup> / <sub>1</sub> in	Shaft diameter
H	36 <sup>1</sup> / <sub>2</sub> in	Housing height
B	43 <sup>0</sup> / <sub>1</sub> in	Length base
≈m	1.852,996 lbs	Peso



Medidas

	S2BCH-1500-FL	Complete unit float
	S2BCH-1500-HD	Complete unit held
	PH-31	Housing designation
A	18 1/4 in	Center height
C	14 1/2 in	Base width
D	2 5/8 in	Base height
E min	26 1/16 in	Base hole distance 1 min
E min	27 5/8 in	Base hole distance 1 max
E 1, min	34 1/16 in	Base hole distance 3 min
E 1, max	35 5/8 in	Base hole distance 3 max
F	11 0/1 in	Base hole distance 2
s	8	# of mounting bolts
s	1 1/4 in	Mounting bolt diameter
	S2BC-1500-FL	Cartridge float bearing
	S2BC-1500-HD	Cartridge held bearing
	S2C-1500	Cartridge
G	13 1/2 in	Length through bore
L	25 1/2 in	Outside diameter cartridge
	17 lbs	Grease capacity
	881.8 lbs	Cartridge weight
	S2B-1500-FL	Bearing float
	S2B-1500-HD	Bearing held
	409.9 lbs	Bearing weight
	1500 Grp	Bearing group
C <sub>r</sub>	385.957 lbf	Capacidad de carga dinámica, radial
C <sub>0r</sub>	761.112 lbf	Capacidad de carga estática, radial
C <sub>a</sub>	16.923 lbf	Capacidad de carga dinámica, axial
D <sub>0</sub>	23 0/4 in	Outside diameter bearing

