



**FAG**

## S2BCH-90MM-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

### Información técnica



#### Medidas principales y datos de rendimiento

d	90 mm	Diámetro del eje
H	≈ 273,05 mm	Housing height
B	≈ 425,45 mm	Length base
≈m	39,916 kg	Peso



## Medidas

	S2BCH-90MM-FL	Complete unit float
	S2BCH-90MM-HD	Complete unit held
	PH-6	Housing designation
A	≈ 125,412 mm	Center height
C	≈ 152,4 mm	Base width
D	≈ 50,8 mm	Base height
E <sub>min</sub>	≈ 355,6 mm	Base hole distance 1 min
E <sub>min</sub>	≈ 381 mm	Base hole distance 1 max
F	≈ 101,6 mm	Base hole distance 2
s	4	# of mounting bolts
s	≈ 19,05 mm	Mounting bolt diameter
	S2BC-90MM-FL	Cartridge float bearing
	S2BC-90MM-HD	Cartridge held bearing
	S2C-308	Cartridge
G	≈ 146,05 mm	Length through bore
L	≈ 203,2 mm	Outside diameter cartridge
	≈ 0,499 kg	Grease capacity
	≈ 18,733 kg	Cartridge weight
	S2B-90MM-FL	Bearing float
	S2B-90MM-HD	Bearing held
	≈ 7,983 kg	Bearing weight
	308 Grp	Bearing group
C <sub>r</sub>	≈ 255.564,288 N	Capacidad de carga dinámica, radial
C <sub>0r</sub>	≈ 354.131,968 N	Capacidad de carga estática, radial
C <sub>a</sub>	≈ 2.962,368 N	Capacidad de carga dinámica, axial
	2.550 1/min	Limiting speed
D <sub>0</sub>	≈ 169,875 mm	Outside diameter bearing
C <sub>0</sub>	≈ 89,611 mm	Width inner ring
B <sub>0</sub>	≈ 48,412 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 06:44:23 UTC

SCHAEFFLER

